

METHOD, SYSTEM, AND PROGRAM FOR
GENERATING A PROGRESS INDICATOR

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

[0001] The present invention relates to a method, system, and program for generating a progress indicator.

2. Description of the Related Art

10 [0002] In network storage systems where multiple host systems access a common storage system on a network, such as a Redundant Array of Independent Disks (RAID) array, users may query the storage system to determine status information. Notwithstanding that users can access information on the status of the storage system, there is a continual need in the art for improved user interfaces that present information on the status of storage
15 systems in a format that is both ergonomical and accessible to the user.

SUMMARY OF THE PREFERRED EMBODIMENTS

[0003] Provided is a method, system, and program for generating a status page to display on a computer display. A request for status information on a resource is received. A
20 determination is made of an operation being performed with respect to the resource. Data is generated to display a progress bar indicating a percent of the operation that has completed. A first part of the progress bar indicates a percent of the operation that has completed and a second part of the progress bar indicates a percent of the operation that has not completed. A determination is made of an attribute of the operation. Data is then
25 generated to display information with one of the first part or second part of the progress bar indicating the determined attribute of the operation.

[0004] In further implementations, the determined attribute is capable of having one of multiple values. The data to display the information indicating the determined attribute further indicates the determined attribute value, wherein different information is displayed for each attribute value.

- 5 [0005] Still further, displaying the first or second part with information comprises displaying the first or second part of the bar in a manner that conveys the information indicating the determined attribute value of the operation. In certain implementations, the information is conveyed by displaying the first or second part of the bar in a color that is associated with the determined attribute value of the operation, wherein there are different
- 10 colors associated with different attribute values.

[0006] In further implementations, the resource comprises a storage device and the operation comprises a formatting operation performed with respect to the storage device.

- [0007] Yet further, the storage device may includes multiple interfaces, wherein each interface is capable of engaging one storage unit. Data is generated to display information
- 15 on the status of each interface with the displayed progress bar. The information is capable of indicating that each interface is empty or includes an available storage unit, wherein the formatting operation is performed with respect to the available storage units engaged with the interfaces.

- [0008] The described implementations provide an improved technique for displaying
- 20 status of an operation performed with respect to a resource by displaying additional attribute information on the operation with the progress bar indicating a percent of the operation that has completed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Referring now to the drawings in which like reference numbers represents corresponding parts throughout:

FIG. 1 is a block diagram illustrating a computing environment in which aspects of the invention are implemented;

FIG. 2 illustrates an example of a display of status information in accordance with implementations of the invention; and

FIG. 3 illustrates logic to generate data to display status information in accordance with implementations of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0010] In the following description, reference is made to the accompanying drawings which form a part hereof, and which illustrate several embodiments of the present invention. It is understood that other embodiments may be utilized and structural and operational changes may be made without departing from the scope of the present invention.

[0011] FIG. 1 illustrates a computing environment in which aspects of the invention are implemented. A host system 2 is capable of communication with a storage system 4 over a network 6, such as a Local Area Network (LAN), Wide Area Network (WAN), Storage Area Network (SAN), the Internet, an Intranet, etc., using a network protocol known in the art, e.g., Ethernet, Fibre Channel, TCP/IP, HyperText Transfer Protocol (HTTP), File Transfer Protocol (FTP), Fibre Channel, etc. The host 2 includes a browser program 8, such as an Hypertext Markup Language (HTML) browser, capable of downloading and rendering content from the storage system 4, which in certain described implementations includes an HTTP server 16 communicating using the HTTP protocol. However, the storage system 4 may use alternative communication protocols known in the art to communicate with devices over the network 6.

5 [0012] The host system 2 may comprise any computer device known in the art capable of communicating over a network 6 and running a web browser program 8, such as a personal computer, workstation, mainframe, server, telephony device, hand held computer, etc. A display monitor 12 is attached to the host 2 and capable of displaying output from the browser program 8.

10 [0013] In one implementation, the storage system 4 comprises a RAID storage system including multiple slots 14a, b, c, d, e, f on a backplane for interfacing with hard disk drives 14b, c, d, e, f as known in the RAID array art. The slots 14a, b, c, d, e, f may comprise an Integrated Drive Electronics (IDE) interface, Small Computer System Interface (SCSI), or any other interface known in the art. FIG. 1 shows one slot 14a of the array having no attached storage device. The storage system 4 further includes a RAID 18 manager including the software and code to manage the hard disk drives 16a, b, c, d, e as a RAID array and perform other RAID management operations known in the art. The RAID manager 18 further includes application programming interfaces (APIs) that are capable of
15 causing the RAID manager 18 to determine the status of the hard disk drives 16a, b, c, d, e, including the status of any rebuilding operations, failures, recovery, etc., in a manner known in the art. The RAID manager 18 would return information to the calling program after executing the APIs.

20 [0014] A status page generator 20 comprises a program that is capable of calling RAID manager 18 APIs to determine the status of physical and logical storage devices in the disks 16b, c, d, e, f and then adding such information to the web page templates 22a, b...n. The generated web pages 22a, b...n including current status information are returned to the requesting host 2 through the HTTP server 16. The status page generator 20 may comprise a Common Gateway Interface (CGI) program, a Java Servlet, or any other
25 application program capable of calling API methods to access data to add to a web page template 22a, b...n.

[0015] In alternative implementations, the web pages 22a, b, c may comprise programs, such as script programs or Java Applets, that execute on the host 2. In such implementations, the program executing on the host 2 may submit the API methods to the storage system 4 to access the status information from the RAID manager 18 directly. In 5 implementations where the program executes on the host, the program may execute within the web browser 8 to display data within the display region of the web browser 8 in a manner known in the art.

[0016] In the described implementations, the RAID manager 18 would include RAID algorithms to rebuild the RAID storage space or logical drive in response to a 10 reconfiguration of the logical array, such as adding or removing storage space, or in response to a failure. If there is a failure of one or more of the hard disk drives 16b, c, d, e, f, then the RAID manager 18 may rebuild the logical storage space using the data and parity information on the surviving disks 16b, c, d, e, f. In the event of a failure, a new disk may be used in the rebuilding operation. The new disk may comprise a hot spare already 15 engaged with a port 14a, b, c, d, e, f or a new disk substituted for the failed disk. The RAID manager 16 is further capable of implementing APIs to access information on the current status of physical and logical disk drives in a manner known in the art.

[0017] FIG. 2 illustrates a page 30 displayed in the monitor 12 by the browser 8 providing status information on the rebuilding operation. The page is generated by the 20 status page generator 20 using RAID manager 18 APIs to access status information. A section 32 labeled "Physical Disks" shows the current status of each of the slots 14a, b, c, d, e. The physical disk section 32 displays slot graphical elements 34a, b, c, d, e, f that provide information on the current status of each slot 14a, b, c, d, e, f. In the example of FIG. 2, the slot graphical element 34a indicates that slot 1 is empty, the slot graphical 25 element 34b indicates that slot 2 includes a hot spare that is not currently used in an active logical array, and slot graphical elements 34c, d, e, f indicate that the slots include disk drives 16c, d, e, f used in a logical array. The slot graphical elements 34a, b, c, d, e, f are

displayed with a slot bar 36a, b, c, d, e, f that is displayed in different colors, where the color in which the bar 36a, b, c, d, e, f is displayed represents a state of the slot. For instance, one color may indicate that the slot is empty, another color may indicate that the slot includes a disk that is a hot spare, i.e., not used in any array, and another color may indicate that the slot includes a disk used in a logical array. Alternatively, one color may indicate that there is no ready disk in a slot 14a, b, c, d, e, f and another color may indicate that there is a ready disk 16b, c, d, e, f in the slot, whether or not the disk is a hot spare or in use in an array.

[0018] The status page 30 further includes a "Logical Disk" section 40 providing status information on an operation performed with respect to the disks 16b, c, d, e, f in an array. The logical disk section 40 displays a progress indicator 42, having a moving portion 44 that moves across a bar 46 as the operation monitored by the progress indicator 42 progresses towards completion. The percentage of the job completed would approximate the percentage length the moving portion 44 extends across the bar 46. The percent the job remains uncompleted is represented as an uncompleted portion 48 color displayed to the right of the moving portion 44 in a different color. The uncompleted portion 48 would extend a percentage length across the bar that is equivalent to the percentage of the job uncompleted. When the operation completes, the entire bar 46 will be displayed as the color of the moving portion 44. In one implementation, the moving portion 44 may be displayed in one color, indicating a percentage of the array that is rebuilt, and the uncompleted portion 48 may be displayed in one of multiple other colors. The different colors used to display the uncompleted portion 48 may convey the reason for the operation being invoked, where different colors may be used to convey different reasons for invoking the operation being monitored by the progress indicator 42.

[0019] For instance, in implementations where the progress indicator 42 monitors the status of an operation rebuilding a disk array, one color used to display the uncompleted portion 48 may indicate that the rebuilding operation is being performed to provide a

different configuration of the storage space assigned to the logical array, such as adding or removing storage space from the logical array. Another color for the uncompleted portion 48 may indicate that the rebuilding operation is performed to rebuild the array after a failure of one of the disks 16b, c, d, e, f.

5 **[0020]** The logical disk section 40 further provides textual information on the operation, such as rebuilding, the array, and array size. If the entire logical array is available to users, then the entire bar 46 would be displayed in a color indicating full availability.

[0021] FIG. 3 illustrates logic implemented in the status page generator 20 to build a page 22a, b...n providing information on the status of the disks 16a, b, c, d, e, f in the
10 RAID array. Control begins at block 100 with the status page generator 20 receiving a request for a page 22a, b...n including status on the physical and logical disks in the storage system 4. In response to the request, the status page generator 20 calls (at block 102) the RAID manager 18 with an API to have the RAID manager determine the status of each slot 14a, b, c, d, e, f in the array. The status page generator 20 then adds slot status
15 information returned by the RAID manager 18 to the pages 22a, b...n to display the information on the status of the slots 14a, b, d, e, f, such as the slot bars 36a, b, c, d, e, f. In certain implementations, the color of the slot bars 36a, b, c, d, e, f indicates the current slot status, i.e., not engaged with a disk, rebuilding, available, etc.

[0022] The status page generator 20 then calls (at block 104) the RAID manager 18 with
20 an API to determine the current status of one or more logical disks, e.g., logical arrays or volumes, implemented in the disk drives 16b, c, d, e, f. If (at block 106) the logical disk is involved in a rebuild operation, then the status page generator 20 calls (at block 108) the RAID manager 18 with an API to determine the amount of disk space rebuilt as a percentage of the total disk space in the logical array. The status page generator 20 then
25 generates (at block 112) data into the page 22a, b...n to display the moving portion 44 extending across a percentage of the bar 46 equivalent to the percentage of the disk space that has been rebuilt. The status page generator 20 further calls the RAID manager 18 with

an API to determine whether the rebuild operation was initiated to reconfigure (add or remove) storage space to the logical disk or as part of a failure recovery operation. Data is added to the page 22a, b...n to display the moving portion 44 of the status indicator in the color associated with the cause of the rebuild operation, e.g., one color may be used to indicate rebuilding is performed to modify or reconfigure the amount of space assigned to the logical disk and another color may be used to indicate rebuilding is performed in response to a failure recovery operation. Still further, additional colors may be used to provide further state information. For instance, one color may be used to indicate that the rebuild operation is being performed to add space to the array and another color used to indicate that the rebuild operation is removing space from the array.

[0023] If (at block 106) the logical disk is not involved in a rebuilding operation, then the status page generator 20 adds (at block 118) data to the page 22a, b...n to display the moving portion 44 in a color indicating that the entire logical array is available for Input/Output (I/O) operations. A refresh tag is added (at block 120) to the generated page 22a, b...n to cause the host browser 8 to automatically periodically access the status page 22a, b...n to obtain more current status and progress indicator 42 data. The HTTP server 16 then transmits (at block 122) the generated status page 22a, b...n to the host web browser 8 for rendering and display at the host display 12.

[0024] The described implementations provide a technique for displaying information on the status of a storage device, such as a RAID array, that integrates different types of information into the display to allow the user to not only view the operation that is occurring, but to also concurrently view information with the progress indicating reasons for the operation and a state that will exist after the operation completes. For instance, in the described storage array implementation, the progress indicator 42 provides information that allows the user to determine the state of the storage system 4 after the operation completes. If the uncompleted portion 48 is displayed in a color that indicates that the rebuild is performed to reconfigure the logical disk, then the user will know that at the end of the

rebuild the logical disk will have a new configuration, e.g., more or less storage space. On the other hand, if the uncompleted portion 48 is displayed in a color associated with failure recovery operations, then the user will know that an error occurred and that after the rebuild operation completes, the system will have recovered from some failure. Other colors may also be used to indicate additional causes or further detail on the rebuild or other operation being tracked by the progress indicator 42 that indicates the state that will exist at the storage system 4 after the rebuild completes. For instance, one color may indicate that the rebuild is being performed to add storage space to the logical disk, and another color may be used to indicate that storage space is being removed.

5

10 [0025] With the described implementations, the moving portion 44 is displayed in a color indicating the state of the system that will exist upon the completion of the operation whose progress is represented by the moving portion 44. In the storage system implementations, the color used to display the moving portion 44 may indicate that the storage space will be available when the operation completes. The uncompleted portion 48 is displayed in the

15 color that indicates the reason that triggered the operation, indicating the current state of the uncompleted portion of the array and also conveying information on the state after the rebuild, i.e., a logical disk that has been reconfigured or recovered from a failure.

Additional Implementation Details

20 [0026] The preferred embodiments may be implemented as a method, apparatus or article of manufacture using standard programming and/or engineering techniques to produce software, firmware, hardware, or any combination thereof. The term “article of manufacture” as used herein refers to code or logic implemented in hardware logic (e.g., an integrated circuit chip, Field Programmable Gate Array (FPGA), Application Specific

25 Integrated Circuit (ASIC), etc.) or a computer readable medium (e.g., magnetic storage medium (e.g., hard disk drives, floppy disks, tape, etc.), optical storage (CD-ROMs, optical disks, etc.), volatile and non-volatile memory devices (e.g., EEPROMs, ROMs,

PROMs, RAMs, DRAMs, SRAMs, firmware, programmable logic, etc.). Code in the computer readable medium is accessed and executed by a processor. The code in which preferred embodiments are implemented may further be accessible through a transmission media or from a file server over a network. In such cases, the article of manufacture in which the code is implemented may comprise a transmission media, such as a network transmission line, wireless transmission media, signals propagating through space, radio waves, infrared signals, etc. Of course, those skilled in the art will recognize that many modifications may be made to this configuration without departing from the scope of the present invention, and that the article of manufacture may comprise any information bearing medium known in the art.

[0027] In the described implementations, the progress indicator 42 displays the percentage of a rebuild operation that has completed. The progress indicator 42 may be used to indicate the percent completed with respect to any other process, where the uncompleted part of the bar 28 would indicate the current state of the monitored system. The operation represented by the moving portion 44 may have been invoked in response to the state represented by the color of the uncompleted portion 48 of the bar 44.

[0028] In the described implementations, the storage system 4 comprised a RAID array of multiple hard disk drives. In alternative implementations, the storage system may comprise other types of storage systems, such as a Direct Access Storage Device (DASD), Just a Bunch of Disks (JBOD), a tape library having backplane interfaces for multiple tape cartridges, optical disk library, etc.

[0029] In the described implementations, the operation monitored by the progress indicator 42 is a rebuild operation. Additionally, the monitored operation may comprise any formatting operation performed with respect to the storage device(s) in the storage system.

[0030] The progress indicator implementation described herein may apply to monitor systems other than storage systems, such as printing systems, application programs, database systems, file systems, and other Input/Output (I/O) devices.

5 [0031] The display of FIG. 2 monitored the status of an operation being performed with respect to a single device, i.e., the storage system 2. Additionally, the progress indicator implementation described herein may monitor the progress of one or more operations on multiple systems.

[0032] In the described implementations, the colors of the moving portion 44 and uncompleted portion 48 were displayed in a color indicating a state of the storage areas
10 represented by the bar 46. For instance, the color of the moving portion 44 indicates that the state of the percent of the storage space rebuilt is available and the color of the uncompleted portion 48 indicates that the state of the storage space is unavailable due to failure or a reconfiguration of the space. Additionally, the color in which the progress indicator is displayed may indicate any other attribute of the resource associated with the
15 moving or uncompleted portion of the bar. Thus, the area of the bar 46 occupied by the moving 44 and uncompleted 46 portions indicate the resources, or percentage of resources, associated with the bar and the color in which the bar is displayed represents a state or attribute associated with the resource on which the operation is performed.

[0033] In the described implementations, the state of the resource associated with the bar
20 portions 44 and 48 was represented by displaying the bar portions 44 and 48 in different color schemes. Alternatively, different techniques may be used to convey the state or attributes associated with the portions 44 and 48, including textual information displayed with the portions 44 and 48, different shapes or designs used for the different portions 44 and 48, etc.

25 [0034] The logic of FIG. 3 is for illustrative purposes. Additional or alternative steps may be performed in addition to those illustrated in the logic. Further, the order of the steps in the preferred logic may also vary.

[0035] The foregoing description of the described implementations of the invention has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. It is intended that the scope of the invention be limited not by this detailed description, but rather by the claims appended hereto. The above specification, examples and data provide a complete description of the manufacture and use of the composition of the invention. Since many embodiments of the invention can be made without departing from the spirit and scope of the invention, the invention resides in the claims hereinafter appended.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000